


## Roulement à rouleaux 20NQI3714-JTEKT - 20NQI3714-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/20nqi3714-koyo>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_1$	$r_{min}$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
25	20	37	14	—	0.3	17.1	19.1	17 000	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
20NQI3714					22	35	0.3	—	0.066	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482378
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	14 mm
Poids	66 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE