


## Roulement à rouleaux NQI28-20-JTEKT - NQI28-20-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nqi28-20-koyo>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>w</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	—	Without inner ring	
32	28	42	20	—	24.3	39.4	14 000	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					d <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> max.	Without inner ring	With inner ring	—
NQI28/20					30	40	0.3	0.070	0.098	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482781
Diam. intérieur	28 mm
Diam. extérieur	42 mm
Épaisseur	20 mm
Poids	98 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE