


Roulement à rouleaux 38NQ4720-JTEKT - 38NQ4720-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/38nq4720-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-----|--------------------------|---------------|-------------------------|--------------------|--|------------------------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 38 | — | 47 | 20 | — | 23.6 | 45.8 | 12 000 | 38NQ4720 |
| | | Mounting dimensions (mm) | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | |
| With inner ring | | d_i max. | D_i max. | r_i max. | Without inner ring | With inner ring | | |
| | | — | 45 | 0.3 | 0.073 | — | — | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952482996 |
| Diam. intérieur | 38 mm |
| Diam. extérieur | 47 mm |
| Épaisseur | 20 mm |
| Poids | 73 g |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE