


Roulement à rouleaux NQ40-15AD-JTEKT - NQ40-15AD-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nq40-15ad-koyo>

Machined ring needle roller bearings

F_w 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
40	—	50	15	—	21.0	35.1	12 000	NQ40/15AD
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d_a	D_a	r_a	Without inner ring	With inner ring		
		min.	max.	max.	—	—		
		—	48	0.3	0.063	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483023
Diam. intérieur	40 mm
Diam. extérieur	50 mm
Épaisseur	15 mm
Poids	63 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE