


Roulement à rouleaux NQI50-25-JTEKT - NQI50-25-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nqi50-25-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F_w	d	D	B	B_1	r_{min}	C_r	C_{10}	Oil lub.	Without inner ring	
55	50	68	25	—	0.6	47.4	90.4	8 900	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NQI50/25					54	64	0.6	—	0.255	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483474
Diam. intérieur	60 mm
Diam. extérieur	68 mm
Épaisseur	25 mm
Poids	255 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE