

## Roulement à rouleaux RNA5916-JTEKT - RNA5916-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/rna5916-koyo>

### Machined ring needle roller bearings Koyo F<sub>W</sub> 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) |    |                          |                     | Basic load ratings (kN) |                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                                    | Bearing No. |
|--------------------------|----|--------------------------|---------------------|-------------------------|--------------------|--|------------------------------------|-------------|
| F <sub>w</sub>           | d  | D                        | B                   | C <sub>r</sub>          | C <sub>10r</sub>   | Oil lub.   | Without inner ring                 |             |
| 90                       | 80 | 110                      | 40                  | 114.0                   | 232.0              | 5 100  | RNA5916                            |             |
|                          |    | Mounting dimensions (mm) |                     |                         | (Refer.) Mass (kg) |  | (Refer.) Applicable inner ring No. |             |
| With inner ring          |    | d <sub>s</sub> min.      | D <sub>s</sub> max. | r <sub>s</sub> max.     | Without inner ring | With inner ring                                    |                                    |             |
|                          |    | 85                       | 105                 | 1                       | 0.681              | 1.09   | IRM809040                          |             |

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952483986 |
| Diam. intérieur | 90 mm         |
| Diam. extérieur | 110 mm        |
| Épaisseur       | 40 mm         |
| Poids           | 681 g         |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE