

Butée à aiguilles AZ355212-IKO - AZ355212-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/butee-aiguille/az355212-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
35	AZ 355212	99	AZK 35525	36	WS 3552	GS 3552	31.5	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d ₄ Min.	D ₄ Max.	N	N	rpm
35	52	12	35.05	51.5	5	3.5	0.6	38	49	49	39	29 100	91 100	7 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060465931
Diam. intérieur	35 mm
Diam. extérieur	52 mm
Épaisseur	12 mm
Poids	99 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE