

# Rotule SI

## DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/sil5-t-k-durbal>


### DSIL5-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated

sliding combination:  
steel / bronze-PTFE composite

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
DSIL	S/T/K	5	M 5	8	6,00	18	8,5	11

type	measurement (mm)			h	d <sub>1</sub>	load rating C <sub>0</sub> (N)	weight (kg)
	l <sub>1</sub> min	W					
DSI / DSIL S/T/K	10	9	27	13	6,0	0,016	

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489070
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE