

Rotule SI SI8-T-K-DURBAL - SI8-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/si8-t-k-durbal>


SI8-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI	BTK	8	M 8	12	9,00	24	12,5	16
type	measurement (mm)		h	d ₁	load rating C ₁₀ (kg)	weight (kg)		
SI / SIL	BTK	16	14	36	14	12,9	0,047	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489148
Diam. intérieur	8 mm
Diam. extérieur	24 mm
Epaisseur	12 mm
Type	SI
Poids	47 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE