

Rotule SI

SIL30-T-K-DURBAL - SIL30-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/sil30-t-k-durbal>


SIL30-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 30 T/K		30	M 30 x 2	37	25,00	70	40,0	50

type	measurement (mm)			d ₁	load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h			
SI / SIL 30 T/K	51	41	110	17	114,0	1,100

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489728
Diam. intérieur	30 mm
Diam. extérieur	70 mm
Epaisseur	37 mm
Type	SI
Poids	1100 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE