

Rotule SA DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/dsal6-t-k-durbal>


DSAL6-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
DSAL 6 T/K		6	M 6	9	6,75	20	

type	measurement [mm]		h	alpha [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
DSA / DSAL 6 T/K	21		36	13	7,7	0,020

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489940
Diam. intérieur	6 mm
Diam. extérieur	20 mm
Epaisseur	9 mm
Type	SA
Poids	20 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE