

Rotule SA

SAL30-T-K-DURBAL - SAL30-T-K-DURBAL

https://www.123roulement.ca/roulement-palier/rotule/sa/sal30-t-k-durbal

SAL30-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SAL 30 T/K | | 30 | M 30 x 2 | 37 | 25,00 | 70 |

| type | measurement [mm] | | | Tragzahlen C ₁₀ [kN] | weight [kg] |
|-----------------|--------------------|----------------|-----|---------------------------------|-------------|
| | l ₁ min | l ₂ | h | | |
| SA / SAL 30 T/K | 66 | 35 | 110 | 17 | 114,0 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952490403 |
| Diam. intérieur | 30 mm |
| Diam. extérieur | 70 mm |
| Epaisseur | 37 mm |
| Type | SA |
| Poids | 1100 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE