

Rotule SA SSA8-T-K-DURBAL - DSSA8-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/dssa8-t-k-durbal>

SSA8-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | |
|------------------|-------------------|------------------|------------------|-----------|---------------------------------|-------------|--|
| SSA 8 T/K | 8 | M 8 | 12 | 9,00 | 24 | | |
| type | measurement [mm] | | h | alpha [°] | load rating C ₀ [kN] | weight [kg] | |
| SSA / SSAL 8 T/K | 25 | 42 | 14 | 12,9 | 0,038 | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952490625 |
| Diam. intérieur | 8 mm |
| Diam. extérieur | 24 mm |
| Epaisseur | 12 mm |
| Type | SA |
| Poids | 38 g |
| Filetage | Filetage à droite |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE