

Rotule SI

DSSIL5-T-K-DURBAL - SSIL5-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/ssil5-t-k-durbal>

DSSIL5-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
DSSIL 5 T/K	5	M 5	8	B	C1	d1	d2	d3	d4
				8	6,00	18	8,5	11	

type	l1 min	W	h	α	load rating C0 [kN]	weight [g]
DSSIL / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491080
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE