

# Rotule SI

## DSSIL8-T-K-DURBAL - SSIL8-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/ssil8-t-k-durbal>

### DSSIL8-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 8 T/K			d	G	B	C1	d1	d2	d3	d4
			8	M 8	12	9,00	24	12,5	16	

type	l1 min	W	h	α [°]	load rating C0 [kN]	weight [kg]
DSSIL / DSSIL 8 T/K	16	14	36	14	12,5	0,047

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491165
Diam. intérieur	8 mm
Diam. extérieur	24 mm
Epaisseur	12 mm
Type	SI
Poids	47 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE