

# Rotule SI

## SSIL14-T-K-DURBAL - SSIL14-T-K-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/ssil14-t-k-durbal>

### SSIL14-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
SSIL 14 T/K	14	M 14	19	13,50	36	20,0	25		

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	W	h	α [°]		
SSI / SSIL 14 T/K	25	22	57	16	31,0	0,160

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491332
Diam. intérieur	14 mm
Diam. extérieur	36 mm
Epaisseur	19 mm
Type	SI
Poids	160 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE