

Rotule SA DSA6-BK-DURBAL - DSA6-BK-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/dsa6-bk-durbal>

DSA6-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free



order number right hand thread / left hand thread	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
DSA 6 BK	6	M 6	9	6,7	21
type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
DSA / DSAL 6 BK	22	36	11	7,65	0,020

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952492391
Diam. intérieur	6 mm
Diam. extérieur	21 mm
Epaisseur	9 mm
Type	SA
Poids	20 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE