

Rotule GE GAR60-UK-2RS-DURBAL - GAR60-UK-2RS-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/ge/gar60-uk-2rs-durbal>


GAR60-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number right-hand thread	d	G	B	C ₁	d ₂
GAR 60 UK-2RS	60	M 52 x 3	44	38,0	135

type	l ₁ min	measurement [mm] l ₂ min	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 60 UK-2RS	115	75	210	6	450,0	5,900

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060467782
Diam. intérieur	60 mm
Diam. extérieur	135 mm
Epaisseur	44 mm
Type	GE
Poids	5900 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1
Norme	Sans norme

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE