

# Rotule SI

## GIR20-UK-2RS-DURBAL - GIR20-UK-2RS-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/gir20-uk-2rs-durbal>

### GIR20-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE fabric

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
no lubrication necessary,  
maintenance free



order number	measurement [mm]	
Right hand thread	d	G
Left hand thread	B	C <sub>1</sub>
<b>GIR 20 UK (-2RS)</b>	20	M 20 x 1,5
	16	13,0
		53
		d <sub>2</sub>
		d <sub>4</sub>
		h
		W

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 20 UK	40	77	32	9	60,0	0,350

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493855
Diam. intérieur	20 mm
Diam. extérieur	53 mm
Épaisseur	16 mm
Type	SI
Poids	350 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE