

# Rotule SI

## GIR25-UK-DURBAL - GIR25-UK-DURBAL

https://www.123roulement.ca/roulement-palier/rotule/si/gir25-uk-durbal

### GIR25-UK



**female thread: maintenance free, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq 35$  with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq 35$  with additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>
GIR 25 UK	25	M 24 x 2	20	17,0	64	33,5	42

  

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIR 25 UK	48	94	36	7	83,0	0,640

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493978
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Épaisseur	20 mm
Type	SI
Poids	640 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE