

Rotule SI

GIR30-UK-DURBAL - GIR30-UK-DURBAL

https://www.123roulement.ca/roulement-palier/rotule/si/gir30-uk-durbal

GIR30-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



order number	measurement [mm]					
GIR 30 UK	d	G	B	C ₁	d ₂	d ₄
	30	M 30 x 2	22	19,0	73	40,0
type	measurement [mm]			load rating	weight	
GIR / GIR 30 UK	t ₃ min	h	W	C ₀ [kN]	[kg]	
	56	110	41	6	110,0	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494005
Diam. intérieur	30 mm
Diam. intérieur	1.181" inch
Diam. extérieur	73 mm
Diam. extérieur	2.874" inch
Epaisseur	22 mm
Epaisseur	0.866" inch
Type	SI
Poids	930 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1
Norme	Sans norme

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE