

Rotule SI

GIL30-UK-2RS-DURBAL - DGIL30-UK-2RS-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/dgil30-uk-2rs-durbal>

GIL30-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C ₁	d ₂	d ₄	
GIL 30 UK (-2RS)			30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494043
Diam. intérieur	30 mm
Diam. extérieur	73 mm
Épaisseur	22 mm
Type	SI
Poids	930 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE