

# Rotule SI

## GIL30-UK-2RS-DURBAL - GIL30-UK-2RS-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/gil30-uk-2rs-durbal>

### GIL30-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>
GIL 30 UK (-2RS)			30	M 30 x 2	22	19,0	73	40,0 50

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494043
Diam. intérieur	30 mm
Diam. extérieur	73 mm
Épaisseur	22 mm
Type	SI
Poids	930 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE