

Rotule SA POSL22-DURBAL - POSL22-DURBAL


<https://www.123roulement.ca/roulement-palier/rotule/sa/posl22-durbal>

POSL22



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

| order number | d | G | measurement [mm] | B | C ₁ | d ₂ |
|--|----|------------|------------------|-------|----------------|----------------|
| right hand thread left hand thread POSL 22 | 22 | M 22 x 1,5 | 28 | 20,00 | 54 | |

| type | measurement [mm] | | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------|--------------------|----|----------|---------------------------------------|----------------|
| | l ₁ min | h | | | |
| POS / POSL 22 | 51 | 84 | 15 | 57,0 | 0,480 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952494739 |
| Diam. intérieur | 22 mm |
| Diam. intérieur | 0.866" inch |
| Diam. extérieur | 54 mm |
| Diam. extérieur | 2.126" inch |
| Epaisseur | 28 mm |
| Epaisseur | 1.102" inch |
| Type | SA |
| Poids | 480 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE