

# Rotule SI

## SIZJL6-DURBAL - SIZJL6-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/sizjl6-durbal>

### SIZJL6



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size 9 with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]						
			d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>
SIZJL 6			6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91

type	inches	h <sub>1</sub> min	measurement [mm]		h	α	load rating	weight
			W			[°]	C <sub>0</sub> (KN)	[g]
SIZJ / SIZJL 6	1 / 4 "	15,88	9,53		33,32	13,5	9,6	0,023

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952496702
Diam. intérieur	6.35 mm
Diam. extérieur	19.05 mm
Epaisseur	9.53 mm
Type	SI
Poids	23 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE