

Rotule SI

SI50-ES-2RS-DURBAL - DSI50-ES-2RS-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/dsi50-es-2rs-durbal>

SI50-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
d	G	B	C ₁	d ₂	d ₃	d ₄	W	
SI 50 ES (-2RS)		50	M 45 x 3	35	30,0	112	62,0	75

type

type	l ₁ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SI / SII 50 ES (-2RS)	68	65	160	6	290,0	3,5

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497549
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Épaisseur	35 mm
Type	SI
Poids	3500 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE