

## Rotule SI SI60-ES-DURBAL - SI60-ES-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/si60-es-durbal>

### SI60-ES



**female thread; lubrication required, according to DIN ISO 12240-4; serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Rod end body: surface zinc plated**

**Sliding combination: steel / steel**

**Inner ring: bearing steel, hardened, ground and phosphated**

**Outer ring: bearing steel, hardened, ground and phosphated**

**Lubrication: lubrication required**

order number	right hand thread	left hand thread	d	G	measurement [mm]				
SI 60 ES			60	M 52 x 3	44	38,0	135	70,0	88

type	l <sub>1</sub> min	measurement [mm]		h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SI60 ES	70	75	175	6		450,0	5,5

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497662
Diam. intérieur	60 mm
Diam. extérieur	135 mm
Epaisseur	44 mm
Type	SI
Poids	5500 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE