

Rotule TAPR GIHO-KL-20DO-DURBAL - DGIHO-KL-20DO-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/tapr/dgiho-kl-20do-durbal>

GIHO-KL-20DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d ₁	d ₂	G	d ₄	B	C ₁	C ₂	
GIHO-KL 20 DO*			20	24,1	55	M 14 x 1,5	25	55	16	13	17

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500690
Diam. intérieur	20 mm
Diam. extérieur	55 mm
Épaisseur	13 mm
Type	TAPR
Poids	430 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE