


Rotule TAPR GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/tapr/giho-kl-40do-durbal>

GIHO-KL-40DO 

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.


Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required



order number	right hand thread	left hand thread	measurement [mm]								
			d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHO-KL 40 DO			40	45,0	100	M 27 x 2	45	90	28	23	23

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 40 DO	105	37	155,0	45	7	156,0	2,16

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500805
Diam. intérieur	40 mm
Diam. extérieur	100 mm
Epaisseur	23 mm
Type	TAPR
Poids	2160 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE