

## Rotule TAPR GIHO-KL-60DO-DURBAL - GIHO-KL-60DO-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/tapr/giho-kl-60do-durbal>

**GIHO-KL-60DO**

**FERROBAL**

*\* without grease nipple*

**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

order number	right hand thread	left hand thread	measurement [mm]								
			d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
GIHO-KL 60 DO			60	66,8	160	M 42 x 2	68	134	44	38	38

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
GIHO-K / GIHO-KL 60 DO	150	57	230,0	68	6	380,0	7,15

### CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500881
Diam. intérieur	60 mm
Diam. extérieur	160 mm
Epaisseur	38 mm
Type	TAPR
Poids	7150 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE