

Rotule GEG

GE12-LO-DURBAL - GE12-LO-DURBAL


https://www.123roulement.ca/roulement-palier/rotule/geg/ge12-lo-durbal

GE12-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring:
bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication:
lubrication required

order number	measurement [mm]				
GE 12 LO	d	B	C	d ₁ min	D
	12	12	7	15,5	22

type	measurement [mm]			d ₁	r ₁	load rating C ₁₀ [N]	weight [kg]
	r ₁₅ min	r ₂₅ min	d ₂				
GE 12 LO	0,3	0,3	18,0	4	53	0,022	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506364
Diam. intérieur	12 mm
Diam. extérieur	22 mm
Epaisseur	7 mm
Type	GEG
Poids	22 g
Lubrification	avec
Conditionnement	-
Norme	Sans norme

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE