

## Rotule GEG GE60-LO-DURBAL - GE60-LO-DURBAL


<https://www.123roulement.ca/roulement-palier/rotule/geg/ge60-lo-durbal>

### GE60-LO



**Description:** spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

**Outer ring:**  
bearing steel, hardened, ground and phosphated, single split in axial direction

**Lubrication:**  
lubrication required

order number	measurement [mm]				
	d	B	C	d <sub>1</sub> min	D
GE 60 LO	60	60	36	68,0	90

type	measurement [mm]		d <sub>2</sub>	α [°]	load rating C <sub>10</sub> [kN]	weight [kg]
	r <sub>15</sub> min	r <sub>25</sub> min				
GE 60 LO	1,0	1,0	80,0	4	1220	1,150

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506517
Diam. intérieur	60 mm
Diam. extérieur	90 mm
Epaisseur	36 mm
Type	GEG
Poids	1150 g
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE