

# Rotule SI

## PF15-00-502-DURBAL - PF15-00-502-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/pf15-00-502-durbal>

### PF15-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3485 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields

order number		measurements (mm)											
type	type load shield	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>				
PF 15 -00	-502	15	19	M 12	17,5	40	16,5	12					
measurements (mm)		weight		calculation factors		rotational speed limit		basic load rating		stat.			
type	h	l	l <sub>1</sub>	r	SW	α	(°)	(kg)	Y	%	v <sub>max</sub> (min)	C (N)	C <sub>0</sub> (N)
PF 15	51	24	20,0	15	17	7,0	0,140	2,30	2,41		1025	5000	1890

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507385
Diam. intérieur	15 mm
Diam. extérieur	40 mm
Épaisseur	16.5 mm
Type	SI
Poids	140 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE