

Rotule SA

PM06-00-502-DURBAL - PM06-00-502-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/pm06-00-502-durbal>

PM06-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

| order number | | measurements [mm] | | measurements [mm] | | weight | | rotational speed limit | | basic load rating | | | | |
|-------------------|----------------|-------------------|----------------|------------------------|----------------|-------------------|----------------|------------------------|----|-------------------|----------------------|----------------|------|-----|
| type | specification | d ₁ | d ₂ | d ₄ | d ₅ | d ₇ | b ₁ | b ₂ | Y | Y ₀ | C | C ₀ | | |
| PM 06 -00 | -502 | 6 | M 10 x 1 | 8,5 | 24 | 14 | 14 | 10 | | | | | | |
| measurements [mm] | | weight | | rotational speed limit | | basic load rating | | dyn. | | stat. | | | | |
| type | l ₁ | l ₂ | l ₃ | h ₁ | h ₂ | u | z | α | α' | [kg] | [min ⁻¹] | [N] | [N] | |
| PM 06 | 42,5 | 17 | 64 | 1,5 | 2,5 | 10,5 | 0,062 | | | 1,28 | 1,34 | 1300 | 2445 | 765 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952507477 |
| Diam. intérieur | 6 mm |
| Diam. extérieur | 24 mm |
| Épaisseur | 14 mm |
| Type | SA |
| Poids | 62 g |
| Filetage | Filetage à gauche |
| Lubrification | avec |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE