

Rotule SA

PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/pm15-00-501-durbal>

PM15-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		rotational speed limit		basic load rating	
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14	
measurements [mm]		weight		rotational speed limit		basic load rating			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17
		weight		rotational speed limit		basic load rating			
Y	Y _c	n _{max} [min ⁻¹]	C	C ₀ [N]	C ₀ [lbf]	C ₀ [kN]	C ₀ [lbf]	C ₀ [kN]	C ₀ [lbf]
			975	5485	3270				

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507620
Diam. intérieur	15 mm
Diam. extérieur	42 mm
Epaisseur	20 mm
Type	SA
Poids	310 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE