

Rotule SA BRM20-60-501-DURBAL - BRM20-60-501-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/sa/brm20-60-501-durbal>

BRM20-60-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3402 D10k (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]							
type	optimal	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h	
BRM 20 -60	-501	20	M 20 x 1,5	24,5	50	25	18,0	78	
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating	
type	l	l ₂	α [°]	Y	Y ₀	Temp. [min.]	C [N]	C ₀ [N]	stat. [N]
BRM 20	47	28	7,0	0,338	2,46	2,58	825	5350	2300

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509198
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	50 mm
Diam. extérieur	1.969" inch
Epaisseur	25 mm
Epaisseur	0.984" inch
Type	SA
Poids	338 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE