

# Rotule SI

## BRF12-60-501-DURBAL - BRF12-60-501-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/brf12-60-501-durbal>

### BRF12-60-501



**rod end housing:**  
stainless steel 1.4534, hardened, bearing race superfinished

**inner ring:**  
stainless steel, hardened, surface superfinished

**lubrication:**  
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number	type	measurements [mm]									
		d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	h
BRF 12 -60 -501		12	17,5	M 12	14,5	32	22	16	12,0	50	
measurements [mm]	type	weight			calculation-factors Y	rotational speed limit v <sub>max</sub> [min]	basic load rating				
		SW	α [°]	[kg]			dyn. C [N]	stat. C <sub>0</sub> [N]			
BRF 12	22	6,5	16	19	7,5	0,107	1,74	1,82	1125	3450	1250

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509273
Diam. intérieur	12 mm
Diam. extérieur	32 mm
Épaisseur	16 mm
Type	SI
Poids	107 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE