


# Rotule SI

## BRF5-8-00-502-DURBAL - BRF5-8-00-502-DURBAL

<https://www.123roulement.ca/roulement-palier/rotule/si/brf5-8-00-502-durbal>

**BRF5/8-00-502** 

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished


**lubrication:**  
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 1/4 and 3/8)  
DIN 71 412 H1 (sizes 1/2 and 1 1/4)


**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**



**female thread:**  
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]										
type	right hand thread	left hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b3	
BRF 5/8 -00		-502	.625	.866	.6250-18 UNF	.744	1.653	1.062	.826	.590		
measurements [inches]		weight	calculation factors	rotational speed limit	basic load rating stat.							
type	h	l	l1	l2	SW	α [°]	weight [kg]	Y	%	rpm	C [N]	C0 [N]
BRF 5/8	2.539	1.102	.322	.885	.866	8.0	0,220	2,24	2,35	975	6250	2350

### CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510163
Diam. intérieur	15.88 mm
Diam. extérieur	41.99 mm
Épaisseur	20.98 mm
Type	SI
Poids	220 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE