


Roulement à bille simple rangée 1620-SS-NICE - 1620-SS-NICE

<https://www.123roulement.ca/roulement-palier/roulement-bille/simple-rangee/1620-ss-nice>

1600 Series™ Precision Ground Radial Bearings NICE



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|-------------------|------------------|-------------------------------|-------------------------------|------------------------------------|------------------------------------|---------------------------------------|---------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| 1620™ | | | | | SS | 0.4375 11.113 | 1.3750 34.925 |
| WIDTH | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
| B (in) (mm) | C (lb) (N) | C ₀ (lb) (N) | W ⁰ (lb) (g) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.4375 11.113 | 1878 8307 | 850 3783 | 0.12 0.05 | 0.658 16.71 | 1.203 30.56 | 0.025 0.64 | |

ⓘ Weights given are for greased and sealed versions

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952557366 |
| Diam. intérieur | 11.113 mm |
| Diam. extérieur | 34.925 mm |
| Épaisseur | 11.113 mm |
| Poids | 50 g |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE