

Roulement à bille simple rangée 3006-DS-NICE - 3006-DS-NICE

<https://www.123roulement.ca/roulement-palier/roulement-bille/simple-rangee/3006-ds-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3006™			DS			+0.005 +0.13 -0.00 -0.013	+0.000 +0.00 -0.0005 -0.013
						0.3750 9.525	0.9063 23.020

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W lb (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	300 1508	300 1335	0.04 0.02	0.517 13.13	0.778 19.76	0.015 0.38

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3006 and larger +0.0005/-0.005 (+/-0.001-0.125)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558226
Diam. intérieur	9.525 mm
Diam. extérieur	23.02 mm
Épaisseur	7.938 mm
Poids	20 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE