


## Roulement à bille simple rangée 5543-V-NICE - 5543-V-NICE

<https://www.123roulement.ca/roulement-palier/roulement-bille/simple-rangee/5543-v-nice>

**5000 Series® Single Row. Unground Flanged Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.			WIDTH	
		A (in) (mm)	B (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5543™	V	+0.005/-0.000 +13/-00	+0.005/-0.000 +19/-00	+0.010/-0.010 +25/-25	0.040 1.02	1.000 25.40	0.088 2.24	0.350 8.89

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
		50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
NO.	SIZE	167	118	80	65	45	32
15	3.18 0.02	743	516	359	289	200	142

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560229
Diam. intérieur	9.53 mm
Diam. extérieur	23.01 mm
2nd Diam. extérieur	25.4 mm
Epaisseur	8 mm
2nd Epaisseur	8.89 mm
Poids	20 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE