


Accessoire de palier ER16-NICE - ER16-NICE

<https://www.123roulement.ca/roulement-palier/paliers/accessoires/er16-nice>

ER Series Precision Ground Radial Bearings with **NICE**
Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "NICE" BEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP FORMING SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO SHARDED CUP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK EDGE FINISH PROVIDES ADDED CORROSION RESISTANCE



PRINCIPLE DIMENSIONS													
BASIC BEARING NUMBER	SHAFT DIAMETER (P) (mm)	OD (mm)	WIDTH (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	J (mm)	K (mm)	M (mm)	RADIUS (mm)
ER16	1	2.0472	1.50	33.64	66.64	36.64	1.2164	3.16	3.64	3.02	7.02	3.4	0.040
	25.40	32	19.29	13.10	21.83	15.48	33.73	4.79	1.19	2.38	5.96	19.29	1.02

RADIAL CAPACITY										WEIGHT			
O (mm)	P (mm)	3-SET SCREWS	BASIC LOAD RATING C (N)	STATIC LOAD RATING Co (N)	50	150	300	500	1200		1800	2500	5000
0.141	2.1784	1/4-28	3145	1770	1012	702	557	489	351	308	274	218	0.86
3.38	37.50		1395	787	453	319	247	207	146	130	121	97	0.31

Shaft tolerance +.0002/-0.005 (+.003/-0.13) For low torque version add suffix "SFF"

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560854
Diam. intérieur	25.4 mm
Diam. extérieur	33.73 mm
Epaisseur	19.05 mm
Poids	310 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE