


Rotule TSM

MX-M10-8-DUNLOP - MX-M10-8-DUNLOP

https://www.123roulement.ca/roulement-palier/rotule/tsm/mx-m10-8-dunlop

MALE ROD ENDS DUNLOP



MALE ROD ENDS

Description:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 80/90 tons/m² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated to 80/90 tons/m² tensile and Phosphated all over

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphate all over

Part No. Right Hand	Part No. Left Hand	D	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MX-M10-8		8	11.0	9.5	11.0	23.8	47.5	31	M10 x 1.50	21	19610

Interchange table

Dunlop	Rose	NMB
MX-M (metric)	RBJ-M	RBJ-M
MX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060550378
Diam. intérieur	8 mm
Diam. extérieur	11 mm
Épaisseur	9.5 mm
Type	TSM
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE