

Rotule SI FXL-M12-CG-DUNLOP - FXL-M12-CG-DUNLOP

<https://www.123roulement.ca/roulement-palier/rotule/si/fxl-m12-cg-dunlop>

FEMALE ROD ENDS DUNLOP

FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 80/90 tons/in² tensile. Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, Heat Treated to 80/90 tons/in² tensile and Phosphate all over. **Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	D	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FXL-M12CG	T2	19.0	16.2	19.0	41.2	54.2	28.0	20.3	M12 x 1.25	22		49030

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060555168
Diam. intérieur	12 mm
Diam. extérieur	19 mm
Epaisseur	16.2 mm
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE