


Rotule SI

DB-SA-174-DUNLOP - DB-SA-174-DUNLOP

https://www.123roulement.ca/roulement-palier/rotule/si/db-sa-174-dunlop

MALE ROD ENDS DUNLOP



DB SERIES: DBM - DBI

Description:
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.
Race: GR-Nylon LV-3H; Balls: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance

Possible Applications:
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles

Temperature Range:
-30°C to +170°C

Specifications:
ELV & RoHS compliant

Housing: Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate

Race: GR-Nylon, LV-3H

Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

| Part No. | Bore Size | C | W | H | D | O | Liner | Static Load Rating (Newtons) Radial |
|-----------|-----------|------|----|------|----|------|----------|-------------------------------------|
| DB-SA-174 | 10 | 65.0 | 14 | 18.5 | 26 | 12.9 | GR-NYLON | 16,760 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DUNLOP |
| N° Ean13 | 3616060557018 |
| Diam. intérieur | 10 mm |
| Diam. extérieur | 65 mm |
| Épaisseur | 14 mm |
| Type | SI |
| Filetage | Filetage à droite |
| Lubrification | avec |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE