

# Rotule GE

## GE300-ES-2RS-DUNLOP - GE300-ES-2RS-DUNLOP

<https://www.123roulement.ca/roulement-palier/rotule/ge/ge300-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

**GEZ ES SERIES**



**Description:**  
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS<sub>2</sub> for increased lubricity on wear surfaces. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS<sub>2</sub>. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

**Features:**  
Metric bore sizes.  
Low cost.  
Maintenance required.  
Up to 140mm bore sizes available.

**Possible Applications:**  
Light to heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Hydraulic applications

**Temperature Range:**  
-34°C to +121°C

**Specifications:**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS<sub>2</sub>

**Balls:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seats:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ300ES-2RS	3	66.675	57.150	120.65	1,500,000

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060558312
Diam. intérieur	76.2 mm
Diam. extérieur	120.65 mm
Épaisseur	66.67 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE