

## Douille à aiguilles BA328-Z-IKO - BA328-Z-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/ba328-z-iko>



| Boundary dimensions |     | mm(inch) |        | Standard mounting dimensions |                   |      |       | mm          |             | Basic dynamic | Basic static | Allowable | Assembled |
|---------------------|-----|----------|--------|------------------------------|-------------------|------|-------|-------------|-------------|---------------|--------------|-----------|-----------|
| $P_w$               | $D$ | $C$      | $d$    | Stuff dia.                   | Housing bore dia. | $C$  | $C_B$ | load rating | load rating | rotational    | inner ring   |           |           |
|                     |     |          |        | Max.                         | Min.              | Max. | Min.  | N           | N           | rpm           |              |           |           |
| 50.800              | 12  | 60.325   | 12.700 | 50.800                       | 2.8               |      |       | 15400       | 24700       | 6000          |              |           |           |

## CARACTÉRISTIQUES PRODUIT

|                  |               |
|------------------|---------------|
| Marque           | IKO           |
| N° Ean13         | 3616060601575 |
| Diam. intérieur  | 50.8 mm       |
| Diam. extérieur  | 60.325 mm     |
| Epaisseur        | 12.7 mm       |
| Vitesse limite   | 6000 rpm      |
| Charge dynamique | 15.4 kN       |
| Charge statique  | 24.7 kN       |
| Conditionnement  | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE