


## Rondelle ondulée fendue SWSW-120.65-111-0.76-5 - SWSW-120.65-111-0.76-5

<https://www.123roulement.ca/accessoire/rondelle/rondelle-ondulee-fendue/swsw-120.65-111-0.76-5>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15 % Newton)  
DB = Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG0475031075S	107,70	0,76	333,617	3,175	120,65	5	7,87

### CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	111 mm
Epaisseur	0.76 mm
Matière	ACIER
Conditionnement	1
Charge à L1	338.065 N
Charge en hauteur	3.175
Diamètre extérieur (max)	120.65 mm
Nombre d'ondes	5

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE