


Rondelle ondulée fendue

SWSW-123.82-111-0.76-5 - SWSW-123.82-111-0.76-5

<https://www.123roulement.ca/accessoire/rondelle/rondelle-ondulee-fendue/sws-123.82-111-0.76-5>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/- 15 % Newton)
Db = Boreing's outside diameter
Dr = Free fit in hole diameter
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG0487029076	111,00	0,76	338,065	3,175	123,82	5	7,37

CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	111 mm
Epaisseur	0.76 mm
Matière	ACIER
Conditionnement	1
Charge à L1	338.065 N
Charge en hauteur	3.175
Diamètre extérieur (max)	123.82 mm
Nombre d'ondes	5

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE