

Pâte à joint

6482-50ML-LOCTITE - 6482-50ML-LOCTITE

<https://www.123roulement.ca/lubrifiant-adhesif/adhesif/pateajoint/6482-50ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Sceroulement
NOM	LOCTITE 6482
CONDITIONNEMENT	F1 50 ml
APPROBATION*	PMUC

Description

LOCTITE® 6482 is a green, low-viscosity, urethane methacrylate, acrylic, retaining compound which has a low halogen and sulphur content and was especially developed for use in the nuclear industry. The product is for bonding cylindrical fitting parts, particularly where strength at elevated temperatures is required. Applications include holding gears and sprockets on to gearbox shafts, and rotors on electric motor shafts. Suits sensitive metals such as titanium.

Avantages

Ideal for retaining cylindrical parts
Offers strength at elevated temperatures
Prevents loosening and leakage from shock and vibration
Low halogen and sulfur content
Suits sensitive metals such as titanium
Positive fluorescence under UV light

Caractéristiques

Acrylic green retaining compound for bonding cylindrical parts that need to withstand elevated temperatures. It has a low halogene and sulphur content for use in nuclear industry

CARACTÉRISTIQUES PRODUIT

Marque	LOCTITE
N° Ean13	3616060813787
Poids	89 g
Conditionnement	-

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE